

# KERALA AGRICULTURAL UNIVERSITY

B.Tech (Food.Engg) 2013 Admission  
II<sup>nd</sup> Semester Final Examination- June -2014

Cat. No: Fden.1202

Title: Heat and Mass Transfer (1+1)

Marks: 50.00

Time: 2 hours

**I Answer the following :-**

(10 x 1=10)

1. Define quantum theory
2. Thermal conductivity
3. Heat exchanger
4. Define emissivity
5. Fourier law
6. Define Stefan Boltzmann's law
7. Differentiate gray body and blackbody
8. Differentiate reflectivity and absorptivity
9. Define Flick's law of diffusion
10. Define critical thickness

**II Write short notes on any FIVE questions**

(5x 2=10)

1. Classification of heat exchangers
2. Analogy between heat transfer and mass transfer
3. Give the application of forced convection
4. Derive the expression for heat transfer through a sphere
5. Differentiate steady state and quasi state flow of heat conduction
6. What do you mean by scaling of heat exchangers
7. Explain the electromagnetic spectrum

**III Write short notes on any FIVE questions**

(5x 4=20)

1. Obtain the expression for log mean temperature difference (LMTD) equation for a single pipe double pass counter flow heat exchanger
2. Prove that heat lost per square meter with reference to outer of a hollow cylinder is  $2K(T_1-T_2) D_2 \log (D_2/D_1)$  where  $T_1$  and  $T_2$  are temperatures and  $D_1$  and  $D_2$  are inner and outer diameter

3. 45kg of oil flows through a 25mm internal diameter copper tube in one second. The oil at the flow condition are  
 specific heat =  $0.49 \text{ kJ/kg}^\circ\text{C}$ , Thermal conductivity =  $0.125 \text{ kJ/hr m}^\circ\text{C}$   
 Kinematic viscosity =  $0.901 \times 10^{-3}$ , Density =  $880 \text{ kg/m}^3$   
 calculate the convection heat transfer coefficient using  $N_{Nu} = 0.023 N_{Re} N_{Pr}$
4. Fruit juice having a specific heat of  $3.85 \text{ kJ/kg}^\circ\text{K}$  is being pre heated from  $5^\circ\text{C}$  to  $45^\circ\text{C}$  in a counter flow double pipe heat exchanger. Heating agent is hot water entering at  $75^\circ\text{C}$  and leaving at  $65^\circ\text{C}$ . The flow rate of fruit juice is  $1.5 \text{ kg/sec}$  and the area of the heat exchanger is  $10.0 \text{ square metre}$ . Calculate the overall heat transfer coefficient.
5. A cold storage room wall  $3 \text{ m} \times 6 \text{ m}$  is constructed of  $150 \text{ mm}$  thick concrete  $K = 1.37 \text{ W/m}^\circ\text{C}$ . Insulation must be provided to maintain a heat transfer rate through the wall at or below  $500 \text{ W}$ . If the thermal conductivity of insulation is  $0.04 \text{ W/m}^\circ\text{C}$ , compute the required thickness of insulation, The outside surface temperature of the wall is  $38^\circ\text{C}$ , and the inside wall temperature is  $5^\circ\text{C}$ .
6. Derive the formula for optimum thickness of lagging for a pipe of inside diameter  $d_1$ .
7. A hollow sphere with inner radius  $R_i$ , outer radius  $R_o$ , inner and outer surface temperature  $t_i$  and  $t_o$  is made of a material whose thermal conductivity is  $K$ . Derive the expression for the conducted heat loss based on the outer area. If  $R_i = 75 \text{ mm}$ ,  $R_o = 125 \text{ mm}$ ,  $K = 52 \text{ W/m}^\circ\text{K}$ , heat conducted out from the sphere is  $118500 \text{ w}$  and inside temperature is  $400^\circ\text{C}$ , determine outside surface temperature.

iv. Answer ANY ONE only.

[1x10=10]

1. Derive the general heat conduction equation in spherical co-ordinates.
2. A furnace wall is composed of  $22 \text{ cm}$  fire brick,  $15 \text{ cm}$  common brick,  $5 \text{ cm}$  of  $85\%$  magnesia and  $3 \text{ mm}$  steel plate on the outside. If the inside surface temperature is  $1500^\circ\text{C}$  and the outside surface temperature is  $90^\circ\text{C}$ . Estimate the temperature between the layers and calculate the heat loss.  $K$  for fire brick  $1.0 \text{ W/m}^\circ\text{K}$ , common brick  $0.7 \text{ W/m}^\circ\text{K}$ , magnesia  $0.06 \text{ W/m}^\circ\text{K}$  and for steel  $45 \text{ w/m}^\circ\text{K}$ .